

RECOMP II USERS' PROGRAM NO. 1084

PROGRAM TITLE:               FIXED POINT OUTPUT SUBROUTINE (RELOCATABLE)  
PROGRAM CLASSIFICATION: Subroutine  
AUTHOR:                       G. V. Roberts  
                              Autonetics  
PURPOSE:                     To output, in fixed point format, normalized  
                              floating point numbers located in memory.  
DATE:                         7 July 1961

Published by  
RECOMP Users' Library  
at  
AUTONETICS INDUSTRIAL PRODUCTS  
A DIVISION OF NORTH AMERICAN AVIATION, INC.  
3400 E. 70 Street, Long Beach 5, Calif.

FIXED POINT OUTPUT SUBROUTINE (RELOCATABLE)

I. PURPOSE

To output, in fixed point format, normalized floating point numbers located in memory.

II. METHOD

The argument is converted to BCD and then typed out. A minus sign is typed for negative numbers; a space is typed for positive numbers.

III. USAGE

3.1 The calling sequence is as follows:

		TRA	$\beta$
$\alpha$		PZE	L(N)
$\alpha+1$		PZE	X
$\alpha+2$		PZE	Y
		Normal return	

where  $\beta$  is the location of the first word of the subroutine, L(N) is the location of the first value, X is the number of values, and Y is the number of values to be typed per line before carriage return. X and Y must be at a binary scale of 18 and 38, respectively.

3.2 To relocate this subroutine, set L7730. Enter the new location in the address portion of the second half, i.e., +0000000 -00XXX00; press "start".

3.3 Including sign and decimal point, each word requires twelve digits, followed by four spaces. The total number of digits typed is ten (see sample typeout).

IV. TIMING

Approximately 3 seconds are required for each value, including computations and typeout.

V. RESTRICTIONS

5.1 The value to be typed out must be less than  $10^7$ .

5.2 When relocating this subroutine, the last two digits of the new location must end in zero (see 3.2).

145.0000000	126.7199999	-0.049999999	-1.255549999	6792000.000
-0.020000000	0.000000000	0.000000000	1.111000000	2.221999999
3.345600000	-123.6488999	16.91999999	-19.99099999	-312940.0999
1000.000000	2000.000000	-3000.000000	-4000.000000	-5000.000000
-6000.220999				